NUCET NUCLEAR ENERGY AND TECHNOLOGY

Nuclear Energy and Technology 11(3): 169–181
DOI 10.3897/nucet.11.157254

Research Article

Ring laser fusion: A novel approach

Ayan Kumar Makar[1]

1 *Plasma Science Society of India (PSSI), Bhat, Gandhinagar: 382428, Gujarat, India*

Corresponding author: Ayan Kumar Makar (icerstark07@gmail.com)

Academic editor: Mahmut Böyükata ♦ **Received** 5 May 2025 ♦ **Accepted** 24 June 2025 ♦ **Published** 16 September 2025

Citation: Makar AK (2025) Ring laser fusion: A novel approach. Nuclear Energy and Technology 11(3): 169–181. https://doi.org/10.3897/nucet.11.157254

Abstract

Laser-induced nuclear fusion offers the tantalizing prospect of a clean, virtually limitless energy source. Traditional inertial confinement fusion (ICF) approaches struggle with challenges in laser efficiency, beam uniformity, and target design. The present research paper proposes a novel method of laser-induced nuclear fusion utilizing a ring laser configuration. The ring laser's unique geometry enables highly focused, omnidirectional energy delivery to a fusion fuel target. This design aims to overcome the limitations of traditional ICF systems by enhancing energy deposition efficiency and increasing compression symmetry.Numerical simulations using specialized codes such as HYADES,LILAC and VORPAL has been used to investigate the potential advantages of this concept.

Keywords

ICF, ring laser, nuclear fusion, numerical simulations

Introduction

The pursuit of clean, virtually limitless energy has made laser-induced nuclear fusion a subject of intense research (Krása and Klír 2020). Laser-induced nuclear fusion, a method that utilizes high-intensity laser pulses to heat and compress fusion fuel to the necessary conditions, has emerged as a leading approach in the field (Ditmire et al. 1999). Among various fusion reactions, Deuterium-Deuterium (D-D) fusion is particularly attractive due to the relative abundance of deuterium and the feasibility of achieving the reaction conditions (Azechi 2016). D-D fusion involves the combination of two deuterium nuclei, isotopes of hydrogen, to produce helium and a neutron, releasing substantial energy in the process. Deuterium-deuterium (D-D) fusion, while challenging, presents advantages over deuterium-tritium (D-T) fusion in terms of reduced neutron production and fuel availability (Madison et al. 2004). However, the realization of controlled D-D fusion has been an elusive goal, hindered by the immense technical challenges associated with reaching and maintaining the necessary conditions for fusion to occur (Peng et al. 2000). Laser-induced fusion has emerged as a promising avenue for achieving controlled nuclear fusion, employing high-intensity lasers to heat and compress the fusion fuel to the required temperatures and pressures (McClarren et al. 2011). Traditional laser fusion approaches have faced challenges in achieving the uniformity and precision in energy delivery essential for initiating and sustaining D-D fusion reactions (Cao et al. 2022). These challenges have necessitated the exploration of innovative technologies to overcome the barriers to efficient and controlled fusion. The advent of laser-induced fusion has marked a significant step forward in the pursuit of controlled nuclear fusion, leveraging high-intensity lasers to heat and compress fusion fuel (Pak et al. 2024). Yet, the optimization of this process, particularly for D-D fusion, requires precise control over energy deposition, an area where traditional laser systems based on inertial confinement fusion (ICF) have encountered inherent limitations in energy efficiency and target

implosion symmetry (Imasaki and Li 2008). It is within this context that ring laser technology presents a novel paradigm, promising enhanced uniformity and control of the irradiation field, critical for advancing D-D fusion research (Bingren 2005). The complexity and costs associated with experimental approaches in fusion research underscore the value of numerical simulations as indispensable tools in the design, analysis, and optimization of fusion experiments (Giuffrida et al. 2020). The current research thus focuses on the application of advanced simulation tools—HYADES, LILAC, and VORPAL—in analyzing the feasibility, dynamics, and efficiency of D-D fusion facilitated by ring laser-based systems (Nieter and Cary 2004).

Literature review

Laser-induced nuclear fusion, particularly inertial confinement fusion (ICF), has long been pursued as an attractive approach for achieving a sustainable and virtually limitless energy source. Extensive research has focused on enhancing the efficiency, symmetry, and overall effectiveness of laser energy deposition onto fusion targets (Atzeni and Meyer-ter-Vehn 2004). However, despite considerable advances, traditional ICF methods continue to face significant technical challenges. These include low laser efficiency, difficulties in achieving uniform beam distribution, and challenges in precise target implosion symmetry (Betti and Hurricane 2016). Previous studies have primarily employed linear or spherical laser geometries, relying heavily on uniform irradiation of fusion pellets to achieve the requisite density and temperature conditions for fusion ignition (Hurricane et al. 2014). For instance, the National Ignition Facility (NIF) employs indirect drive ICF, wherein laser beams irradiate the interior walls of a hohlraum, generating X-rays to symmetrically implode a fuel capsule (Lindl et al. 2004). However, energy losses, beam imprint, and hydrodynamic instabilities significantly impact the success of ignition experiments under these traditional configurations (Hohenberger et al. 2012). Recent advancements have explored alternative geometric configurations and advanced focusing methods to alleviate some of these critical issues. For example, fast ignition approaches attempt to decouple the compression and heating phases using separate lasers or electron beams to enhance ignition efficiency (Tabak et al. 1994; Kodama et al. 2001). Despite these innovations, achieving consistent and scalable results remains elusive.The concept of ring lasers, while well-established in optics for various applications including gyroscopes and spectroscopy, has seldom been explored within nuclear fusion contexts (Sagnac 1913; Post 1967). Ring lasers possess inherent advantages in their unique geometry, such as omnidirectional beam propagation and enhanced coherence properties, which theoretically offer improved symmetry and higher precision in energy delivery (Diels and Arissian 2011). Leveraging these intrinsic advantages, the present study proposes the use of a ring laser configuration specifically tailored for nuclear fusion applications.The current work differentiates significantly from prior efforts by employing numerical simulation tools—namely HYADES, LILAC, and VORPAL—to systematically assess the ring laser's potential in achieving enhanced energy deposition and improved implosion symmetry compared to conventional ICF methods. HYADES simulations have been previously validated for various laser-target interactions and plasma hydrodynamics scenarios (Larsen and Lan 1994), while LILAC and VORPAL are recognized for their efficacy in handling complex physical processes involving laser-plasma interactions and kinetic phenomena (Bell et al. 2008; Craxton et al. 2015). The field of laser-induced nuclear fusion has continuously evolved with extensive theoretical, computational, and experimental investigations dedicated to enhancing the efficiency and viability of fusion processes. Researchers have predominantly focused on refining target implosion dynamics, laser energy delivery techniques, and the optimization of fusion gain through various innovative configurations and methodologies.A pivotal aspect of enhancing laser-driven fusion has been the improvement of laser beam quality and uniformity. Lehmberg and Rothenberg (2000) extensively examined beam smoothing techniques, including spectral dispersion and polarization smoothing, significantly contributing to uniform target irradiation, thereby minimizing hydrodynamic instabilities. Further extending this effort, Michel et al. (2009) conducted extensive studies on cross-beam energy transfer (CBET), which plays a critical role in energy redistribution in plasma, affecting implosion symmetry and efficiency.Advanced computational modeling has substantially contributed to the understanding and prediction of fusion outcomes. Zimmerman and Kruer (1975) pioneered foundational plasma modeling, laying the groundwork for contemporary hydrodynamic codes essential for simulating inertial confinement fusion dynamics. Their initial frameworks have evolved into sophisticated codes like HYDRA, explored by Marinak et al. (2001), which efficiently integrate hydrodynamic and radiative processes critical for precise fusion simulation. Innovative approaches in fusion ignition methodologies, such as fast ignition (FI) and shock ignition (SI), have been extensively explored. Specifically, the fast ignition scheme proposed by Tabak et al. (1994) sparked significant research into using ultra-intense lasers for targeted heating, which was experimentally validated by Kodama et al. (2002), demonstrating substantial progress toward ignition through distinct compression and heating phases. Similarly, Nora et al. (2015) further explored shock ignition, proposing that a separate intense laser spike could enhance ignition conditions significantly by inducing stronger shock waves in fusion targets.Investigations by Colaïtis et al. (2019) and Hohenberger et al. (2012) explored the integration of advanced diagnostics and simulation techniques to analyze implosion dynamics more comprehensively, providing critical insights into instability mitigation strategies and precise control over implosion uniformity. These studies underscored the

importance of accurately modeling and experimentally validating laser-plasma interactions.Recent contributions from Moody et al. (2022) have detailed studies focused on mitigating hydrodynamic instabilities through improved capsule designs and tailored pulse shaping, emphasizing the correlation between beam control precision and successful fusion ignition. Similarly, Trickey et al. (2024) highlighted advanced theoretical frameworks addressing the intricacies of implosion asymmetries and suggested design improvements utilizing multidimensional simulation tools for greater fidelity.In parallel, emerging laser technologies have offered novel opportunities to surpass traditional limitations. Recent works by Xuezhi et al. (2020) introduced the concept of chirped pulse amplification (CPA), revolutionizing ultra-high-intensity laser capabilities essential for fast ignition scenarios. Such advancements underscore the importance of novel laser configurations, resonating with the ring laser geometry proposed in the current manuscript. The current manuscript on ring laser fusion builds substantially on these historical and contemporary advancements by integrating an innovative geometric approach with sophisticated numerical simulations. By employing ring laser configurations, this work uniquely addresses persistent symmetry and efficiency challenges highlighted across previous research, advancing the field towards more robust, efficient, and reliable laser-induced fusion methodologies.

Theory

The theoretical foundation of ring laser-induced nuclear fusion can be elaborated by considering the detailed physical processes involved in energy deposition, plasma compression, and fusion ignition within a target. Starting from basic principles, we first define the energy interaction of laser beams with the plasma target material, which is predominantly governed by electromagnetic wave absorption and hydrodynamic processes.Considering a circular or ring laser geometry, the intensity distribution, I(r), at a radius r from the center of the fusion target can be expressed mathematically by the cylindrical symmetry of the ring laser system as:

$$\mathrm{I}(\mathrm{r}) = \frac{P}{2\pi r h} \tag{1}$$

where P is the total power of the laser and h is the effective height of the cylindrical interaction zone defined by the laser's vertical coherence (Siegman 1986). Energy deposition into the target is primarily governed by inverse Bremsstrahlung absorption, described by the absorption coefficient α, given as (Atzeni and Meyer-ter-Vehn 2004):

$$\alpha = \frac{z^2 e^6 n_e n_i}{3(2\pi)^{3/2}\varepsilon_0^3 m_e^{1/2}(k_B T_e)^{3/2} c\omega^2}\ln\Lambda \tag{2}$$

where Z is the ion charge state, e the electron charge, n_e and n_i are electron and ion densities, ε_0 the permittivity of free space, m_e electron mass, k_B Boltzmann's constant, T_e electron temperature, c the speed of light, ω angular frequency of laser, and lnΛ Coulomb logarithm.

The absorbed power density Q_{abs} thus becomes (Lindl et al. 2004):

$$Q_{abs}(\mathrm{r}) = \alpha \mathrm{I}(\mathrm{r}) e^{-\alpha z} \tag{3}$$

Where z is the propagation depth of laser radiation into the target material. The absorbed energy leads to plasma heating and target compression, described hydrodynamically by the Euler equations, specifically in cylindrical coordinates appropriate for the ring laser geometry (Drake 2006):

Mass Conservation: $$\frac{\partial \rho}{\partial t} + \nabla \cdot (\rho \boldsymbol{u}) = 0 \tag{4}$$

Momentum Conservation:

$$\rho\left(\frac{\partial \boldsymbol{u}}{\partial t} + \boldsymbol{u}.\nabla \boldsymbol{u}\right) = -\nabla \mathrm{p} + f_{\mathrm{laser}} \tag{5}$$

Energy Conservation:

$$\frac{\partial}{\partial t}(\rho e) + \nabla \cdot ((\rho e + p)\boldsymbol{u}) = Q_{abs}(\mathrm{r}) \tag{6}$$

Here, ρ is plasma density, u is fluid velocity, p plasma pressure, e internal energy per unit mass, and f_{laser} is force density due to radiation pressure exerted by the ring laser. The fusion reaction rate Rf, which is the central quantity of interest, can be obtained using standard reaction kinetics from plasma physics (Bosch and Hale 1992):

$$R_f = \frac{n^2}{2}\langle \sigma v \rangle \tag{7}$$

Where n is fuel ion density, and ⟨σv⟩ is the velocity-averaged fusion cross-section, often approximated by empirical fits such as the Bosch-Hale parameterization:

$$\langle \sigma v \rangle = C_1 \xi^{-5/6} e^{-3\xi^{1/3}} \tag{8}$$

Where $\xi = \frac{E_G}{k_B T}$, E_G being the Gamow energy, and C_1 a constant derived from experimental data for specific fusion reactions (Bosch and Hale 1992). Integrating these reaction rates over the compressed plasma volume V, the total fusion yield Y for a given pulse duration τ can be calculated as (Atzeni and Meyer-ter-Vehn 2004):

$$Y = \int_0^\tau \int_V R_f dV dt \tag{9}$$

Finally, to assess ignition criteria and overall efficiency of this ring laser fusion approach, the Lawson criterion has been considered which necessitates that the product of plasma density, confinement time, and temperature exceeds a threshold value specific to the chosen fusion reaction (Lawson 1957):

$$n\tau T \geq (n\tau T)_{crit} \quad (10)$$

By precisely evaluating these equations through numerical simulations employing HYADES, LILAC, and VORPAL codes (Biedron et al. 2000), one can systematically investigate and optimize the conditions required for successful and efficient nuclear fusion using ring laser configurations (Sudan 2009).

Methodology

To investigate the effects of a ring laser configuration on deuterium-deuterium (D-D) nuclear fusion dynamics and efficiency, a comprehensive simulation framework was employed that integrated the HYADES, LILAC, and VORPAL codes. Each simulation tool was selected to leverage its unique capabilities, thereby enabling a multiscale, multidimensional understanding of the fusion process initiated by ring laser energy deposition. The simulation process began with the use of HYADES, a one-dimensional Lagrangian radiation-hydrodynamics code. HYADES was configured to model the initial implosion dynamics of the fusion target under a laser pulse shaped to represent a ring geometry. While HYADES is inherently one-dimensional, a spatially varying energy deposition profile was applied using Gaussian functions to approximate the radial symmetry of the ring laser. This approach enabled the accurate simulation of ablation dynamics, shock formation, and target compression along a single axis. The code tracked the temporal evolution of key plasma parameters, including pressure, temperature, and density, and provided essential insights into the hydrodynamic behavior and compression efficiency of the target under idealized, symmetric energy deposition. Following the HYADES simulations, LILAC, a two-dimensional Eulerian radiation-hydrodynamics code developed by the Laboratory for Laser Energetics, was employed to capture the azimuthal asymmetries and hydrodynamic instabilities introduced by the ring laser configuration. The energy deposition profile derived from the ring laser geometry was input into LILAC to model the evolution of the target in cylindrical coordinates. These simulations were designed to resolve the growth of Rayleigh–Taylor and Richtmyer–Meshkov instabilities during the target's acceleration phase, as well as to assess the degree of non-uniformity in hot spot formation and fuel compression. LILAC's higher dimensional fidelity allowed for a more realistic analysis of how ring-shaped illumination affects the symmetry of the implosion and the onset of plasma instabilities, both of which are critical for achieving optimal fusion conditions. To further investigate kinetic-scale effects and fully three-dimensional plasma behavior, the simulation workflow was extended using VORPAL (now known as VSim), a fully electromagnetic, relativistic particle-in-cell (PIC) code. VORPAL was used to simulate the intricate behavior of charged particles within the plasma, including the effects of collisionless transport, velocity-space anisotropies, and collective electromagnetic phenomena that emerge due to non-uniform energy input from the ring laser. Three-dimensional models were constructed to represent the full geometry of the ring laser interaction with the target plasma. In these simulations, VORPAL resolved the evolution of electric and magnetic fields, particle trajectories, and kinetic instabilities such as filamentation and Weibel modes. Additionally, fusion reaction rates were computed by tracking ion collisions and the resulting neutron generation in real-time, allowing for a detailed estimation of energy yield and reaction efficiency under varying ring laser parameters. The simulation process was carried out in a sequential and interlinked manner, beginning with the 1D hydrodynamic assessment using HYADES, followed by 2D asymmetry modeling with LILAC, and culminating in 3D kinetic simulations with VORPAL. Data from each simulation phase informed the configuration and refinement of subsequent models, ensuring consistency across spatial scales and physical regimes. This integrated, multi-code simulation strategy provided a comprehensive understanding of the ring laser-induced nuclear fusion process and enabled the identification of optimal conditions for maximizing D-D fusion yield and energy output.

Simulation setup

A spherical D-D target is irradiated by a ring laser (Fig. 1) with parameters: number of lasers (N), energy per pulse (E_{pulse}), pulse duration (τ) and wavelength (λ). These parameters are varied to study their impact on the fusion process. To evaluate the feasibility of achieving deuterium-deuterium (D-D) fusion using a ring laser configuration, a three-tier simulation strategy was developed, integrating progressively advanced numerical tools: HYADES, LILAC, and VORPAL. This setup enabled the capture of hydrodynamic compression, multidimensional asymmetries, and kinetic instabilities essential to understanding fusion performance under non-uniform laser irradiation.



Figure 1. Indirect drive fusion process in which the fusion pellet kept inside a hohlraum to smooth out the irradiation where the driver is the ring laser beams introduced via perforation for facilitating radiative equilibrium.

Simulation framework and physical modeling

The numerical simulation of ring laser-induced nuclear fusion for deuterium-deuterium (D-D) target fuel requires a comprehensive computational framework that accurately captures the complex physics governing laser-plasma interactions and fusion dynamics through specialized simulation codes. This simulation setup encompasses two critical components that define the foundation of any successful inertial confinement fusion (ICF) modeling effort: the precise specification of target geometry and initial plasma conditions, and the detailed characterization of the laser system configuration. The integration of these elements is essential for achieving predictive accuracy in fusion simulations, particularly when employing state-of-the-art codes such as HYADES, LILAC, and VORPAL, each offering unique capabilities for multi-physics modeling of laser-driven fusion processes

Target design and initial conditions

The fusion target in all simulations consisted of a single-material spherical deuterium fuel pellet with the following specifications:

- Target radius: 1 mm
- Initial density: 0.1 g/cm³
- Initial temperature: 100 eV
- Material: Pure deuterium

The target was initially at rest, with no internal motion or pre-seeded instabilities. Energy was deposited using a ring laser configuration designed to irradiate the target laterally rather than spherically, promoting equatorial compression.

Laser Configuration

The laser pulse used in all simulations was defined by:

- Peak intensity: 1×10^{15} W/cm^2
- Pulse duration: 1 ns (Gaussian temporal profile)
- Geometry: Ring-focused intensity centered on the equator of the spherical target

This geometry was chosen to simulate lateral convergence and drive fusion conditions from ring-induced implosion, allowing the study of fusion dynamics under non-uniform but symmetric laser irradiation.

Simulation phases and code integration

The complex, multi-scale physics governing ring laser-induced nuclear fusion necessitates a sophisticated simulation strategy. No single computational tool can adequately capture the vast range of physical processes, from the initial laser-plasma interaction at the microscopic level to the macroscopic hydrodynamic compression of the fuel target. To address this challenge, a multi-phase, integrated simulation approach that leverages the specialized capabilities of three distinct codes:LILAC, VORPAL, and HYADES have been adopted. The simulation is conceptually divided into three sequential phases, with data being passed between codes to ensure a self-consistent and comprehensive model of the entire fusion process.

HYADES – 1D hydrodynamic baseline

The first simulation phase employed HYADES, a one-dimensional Lagrangian radiation-hydrodynamics code, to establish a theoretical upper-bound for implosion performance under idealized spherical symmetry. While the ring laser cannot be directly represented in one dimension, the energy deposition was radially distributed to approximate the symmetric inward compression driven by laser ablation.

- Mesh resolution: 500 radial zones
- Physics models: Inverse bremsstrahlung absorption, multigroup radiation transport, SESAME EOS
- Key outputs:
  - Peak ion temperature: ~12 keV
  - Maximum core density: ~45 g/cm³
  - Estimated neutron yield: 1.1×10^{10} neutrons per pulse

These results serve as an ideal baseline, without accounting for asymmetry or multidimensional effects.

LILAC – 2D asymmetry and instability modeling

The second phase of the simulation was conducted using LILAC, a two-dimensional Eulerian radiation-hydrodynamics code operating in cylindrical (r-z) coordinates. This allowed for direct modeling of the ring laser geometry and associated non-uniformities in energy deposition and target response.

- Grid resolution: 600 × 800 (radial × axial)
- Laser modeling: Ray-traced energy deposition focused at the equator
- Instabilities: Rayleigh–Taylor and Richtmyer–Meshkov growth seeded and resolved
- Key outputs:
  - Peak ion temperature: ~9 keV
  - Peak density: ~35 g/cm³
  - Neutron yield: 7.8×10^{9} neutrons per pulse

The LILAC simulation revealed the onset of interface instabilities and slight axial deformation in the hotspot, reducing implosion symmetry and neutron production relative to the ideal 1D case.

VORPAL – 3D kinetic and electromagnetic dynamics

The final simulation phase used VORPAL (VSim), a three-dimensional particle-in-cell (PIC) code capable of resolving field-plasma interactions and kinetic phenomena. This phase modeled the full spatial geometry of the ring laser and the evolving electromagnetic fields within the target.

- Simulation domain: 1 mm³
- Grid resolution: ~1 μm, with ~1000 particles per cell

- Laser implementation: Ring-structured electromagnetic pulse injected from lateral boundaries
- Physics models: Full Maxwellian field solver, Nanbu collision model, binary fusion tracking
- Key outputs:
  - Peak ion temperature: ~8.5 keV
  - Maximum density: ~30 g/cm³
  - Neutron yield: 6.5×10^9 neutrons per pulse
  - Additional observations:
    - Weibel and filamentation instabilities
    - Anisotropic neutron emission aligned along ring symmetry axis
    - Self-generated magnetic fields (~several kT)

Table 1. Summary of Simulation Setup and Conditions

Code	Dimensionality	Laser Geometry	Peak T (keV)	Peak ρ (g/cm³)	Neutron Yield (n/pulse)	Observations
HYADES	1D	Spherical (ideal)	12	45	1.1×10^{10}	Ideal compression, no asymmetry
LILAC	2D (r-z)	Ring (equatorial)	9	35	7.8×10^9	RT instabilities, slight asymmetry
VORPAL	3D	Full ring EM	8.5	30	6.5×10^9	Weibel instability, kinetic effects, anisotropy

The multi-tiered simulation setup developed in this study successfully demonstrates that deuterium-deuterium (D-D) nuclear fusion is achievable using a ring laser configuration. Through the integrated use of HYADES, LILAC, and VORPAL, this approach captures the full spectrum of physical phenomena—from idealized hydrodynamic compression to real-world asymmetries and fully kinetic electromagnetic behavior.

The one-dimensional HYADES simulations established a theoretical performance ceiling, confirming that under symmetric compression, fusion-relevant conditions (temperature ~12 keV, density ~45 g/cm³) can be attained with substantial neutron yield. The LILAC simulations extended this understanding by accounting for geometric asymmetries introduced by the ring laser configuration. They revealed moderate instability growth and reduced symmetry but still produced peak conditions (T ~9 keV, ρ ~35 g/cm³) well within the fusion-viable regime. Finally, the VORPAL simulations introduced a realistic three-dimensional kinetic perspective, resolving field generation, particle interactions, and anisotropic neutron emission. Despite more complex dynamics and energy dispersion, VORPAL still confirmed fusion viability with ion temperatures of ~8.5 keV and yields exceeding 6×10^9 neutrons per pulse.The consistent convergence of results across all three simulation platforms strongly validates the ring laser configuration as a credible driver for inertial confinement fusion.This comprehensive simulation setup confirms that fusion-relevant conditions are consistently achieved across all codes, validating that a ring laser configuration can successfully compress a D-D fuel target to initiate nuclear fusion.

Simulation procedure

The simulation of Ring Laser Induced Nuclear Fusion is a meticulous process that begins with a comprehensive conceptualization of both the laser system and the fusion target. This initial phase, termed the Simulation Setup, establishes the foundational parameters for the entire computational experiment.The Target Design is a critical first step. For this study, a deuterium-deuterium (D-D) fuel pellet is chosen. The selection of D-D fuel is driven by its relatively high fusion cross-section, which, while lower than D-T, allows for a more accessible study of fusion dynamics without the complexities associated with tritium handling. The specific geometry of this pellet, typically spherical, is crucial for achieving uniform compression.Following the target design, the Laser Configuration is defined. A ring laser configuration is employed, designed to deliver energy uniformly to the target's surface. This concentric arrangement of laser beams is intended to minimize asymmetries during the implosion, thereby maximizing compression efficiency. Next, the Initial Conditions of the target are precisely set. The D-D fuel pellet is assumed to be initially at rest, a standard assumption for quiescent targets prior to laser interaction. Its initial density and temperature profiles are specified to represent a realistic starting state for the cryogenic fuel.Finally, the detailed Simulation Parameters are established, dictating the nature of the laser pulse and the initial state of the target. The laser intensity is set at 10^{15} W/cm², a value typical for direct drive inertial confinement fusion experiments, ensuring sufficient energy flux for significant ablation and compression. The pulse duration is a concise 1 ns, a common timescale for high-power laser facilities, allowing for rapid energy delivery before significant hydrodynamic instabilities can fully develop. The target radius is set at 1 mm, representing a manageable size for current simulation capabilities while still being relevant to experimental scales. The initial density of the D-D fuel is 0.1 g/cm³, characteristic of solid or cryogenically frozen deuterium. The initial temperature is 100 eV, indicating a preheated state or the initial energy content of the fuel. With these meticulously defined parameters, the simulation is ready to proceed to the computational phases using specialized codes.Therefore The simulation setup involves the following steps:

i) Target Design: A deuterium - deuterium (D-D) fuel pellet is chosen for its high fusion cross-section.
ii) Laser Configuration: A ring laser configuration is used to uniformly compress the target.
iii) Initial Conditions: The target is initially at rest with specified density and temperature profiles.
iv) Simulation Parameters : Laser Intensity: 10^{15} W/cm², Pulse Duration: 1 ns, Target Radius: 1 mm, Initial Density: 0.1 g/cm³, Initial Temperature: 100 eV.

The simulation begins with the design of a spherical deuterium fuel pellet, chosen for its relatively high D-D fusion cross-section and simplicity in modeling binary fusion reactions. The target consists solely of deuterium and has a radius of 1 mm, representing a typical inertial confinement fusion (ICF) capsule. The initial conditions of the target are defined by a uniform mass density of 0.1 g/cm^3 and a temperature of 100 eV, corresponding to a cold, uncompressed plasma state. The pellet is initially at rest, with no internal velocity or pressure gradients, to isolate the effects of laser-driven compression on the fusion process.The target is irradiated using a ring laser configuration designed to deliver symmetric lateral compression, ensuring a high degree of uniformity in the energy deposition. The laser intensity peaks at 10^{15} W/cm^2, and the pulse is temporally shaped as a Gaussian with a full duration of 1 nanosecond. This configuration is selected to maximize coupling efficiency while minimizing laser-plasma instabilities in the pre-compression phase. The laser energy is absorbed via inverse bremsstrahlung, which dominates the heating mechanism in the underdense corona surrounding the target surface.The first stage of simulation is performed using HYADES, a one-dimensional Lagrangian radiation-hydrodynamics code. The spherically symmetric nature of HYADES allows the modeling of idealized compression dynamics under uniform irradiation. A high-resolution radial mesh is used to capture the formation and inward propagation of the laser-driven shock wave, as well as the subsequent compression of the fuel core. The code incorporates multigroup radiation transport to simulate thermal energy redistribution by photons and models the ablation of the outer shell, which drives the implosion through rocket-like momentum conservation. As the target compresses, temperatures and densities rise in the core, initiating D-D fusion reactions. Reaction rates are calculated based on local ion temperatures and densities using standard cross-section models. The output from the HYADES simulation includes temperature and density profiles, shock timing, neutron production rates, and total fusion energy yield. These results provide a baseline for comparison with more complex multidimensional models.The second phase of the simulation is carried out using LILAC, a two-dimensional axisymmetric radiation-hydrodynamics code, which is employed to capture the effects of the ring laser geometry more accurately. The spatial distribution of laser intensity is configured to simulate a ring-shaped beam focused along the equatorial region of the target. Ray-tracing techniques are used to model the angular incidence and deposition of laser energy onto the target surface. The target mesh is refined in both radial and axial directions to resolve hydrodynamic instabilities and asymmetries arising from the non-uniform irradiation. As in the 1D case, inverse bremsstrahlung is used for laser absorption, and multigroup radiation transport is included to model photon energy flow. During the compression phase, LILAC resolves the development of instabilities such as Rayleigh–Taylor and Richtmyer–Meshkov at the ablation front and the fuel–shell interface. These instabilities can perturb the symmetry of the implosion and degrade hotspot formation, both of which are critical to fusion efficiency. Fusion reactions are again restricted to D-D channels, and the two-dimensional simulation computes local neutron production and energy output as a function of spatial asymmetry. LILAC provides insights into how the ring laser geometry affects hotspot stability, core compression, and directional neutron emission.To capture three-dimensional effects, kinetic behavior, and electromagnetic field interactions, the final stage of the simulation is performed using VORPAL (VSim), a fully electromagnetic particle-in-cell (PIC) simulation framework. The 3D simulation domain spans the full target volume and includes micrometer-scale resolution to accurately model kinetic effects, particularly those not captured by fluid-based hydrodynamics. The laser profile is introduced directly into the simulation as a ring-shaped electromagnetic wave with a vector potential matching the experimental configuration. Electrons and deuterons are modeled as macroparticles, and the system is evolved using a relativistic Maxwell solver. Coulomb collisions are included using the Nanbu binary model, allowing ion heating and thermalization processes to evolve self-consistently. Fusion reactions are implemented by tracking D-D collisions and applying probabilistic models based on the fusion cross-section at given center-of-mass energies.VORPAL simulations reveal the onset of kinetic plasma instabilities such as Weibel and filamentation, as well as self-generated electric and magnetic fields that can influence ion confinement and hotspot behavior. As with the other stages, only D-D fusion reactions are simulated. The primary outputs include spatial and temporal neutron generation maps, energy spectra of fusion products, and time-resolved field structures. These results enable a detailed assessment of how kinetic effects and field dynamics affect the final neutron yield and the efficiency of D-D fusion in a ring-laser-driven configuration.

Data analysis

The simulation data collected from HYADES, LILAC, and VORPAL were analyzed to evaluate the performance of D-D fusion under a ring laser configuration, focusing on key parameters such as core compression, temperature evolution, instability growth, and neutron yield. Each simulation platform contributes unique insights at different scales and dimensionalities, which together build a comprehensive picture of the fusion process.The one-dimensional HYADES simulations provided a baseline for the ideal symmetric implosion dynamics. Time-resolved data on temperature, density, and pressure were extracted at various radial locations within the fuel pellet. The peak ion temperature achieved during compression reached approximately 12 keV, while the core density rose to values exceeding 40 g/cm^3 before stagnation. These values are consistent with conditions favorable for significant D-D fusion reactivity. The fusion reaction rate was computed locally based on the temperature-dependent D-D cross-section, and the resulting neutron yield was

integrated over time to obtain a total yield per pulse. A Gaussian-shaped pulse with a 1 ns duration led to a neutron yield on the order of 10^{10} neutrons per pulse, aligning with theoretical expectations for the given energy input and target size.In the two-dimensional simulations conducted using LILAC, spatial asymmetries were examined by tracking deviations in hotspot location and the uniformity of the imploding shell. Contour plots of temperature and density revealed that the ring laser geometry, while largely effective in achieving equatorial symmetry, introduced axial non-uniformities that slightly elongated the core. Rayleigh–Taylor instabilities were observed at the ablation front, developing prominently during the deceleration phase of the implosion. These instabilities caused small-scale rippling at the fuel–shell interface, reducing the peak compression by approximately 10% compared to the one-dimensional case. The neutron yield was correspondingly reduced, with a maximum yield measured at approximately 7.8×10^{9} neutrons per pulse.Despite this reduction, the LILAC results confirmed that the ring laser configuration successfully delivered significant energy into the core while maintaining quasi-uniform compression.Three-dimensional kinetic data from VORPAL allowed for deeper analysis of nonthermal effects, particle velocity distributions, and electromagnetic field evolution. Phase space diagnostics revealed the formation of anisotropic velocity profiles in both electrons and ions, primarily induced by localized electric fields near the laser interaction region. Field plots showed the emergence of Weibel-like filamentation structures, which contributed to localized magnetic field generation in the order of several kilotesla. These self-generated fields were found to influence the confinement of charged fusion products and alter ion thermalization pathways. The neutron yield estimated from binary fusion events in VORPAL was approximately 6.5×10^{9} neutrons per pulse, slightly lower than in LILAC, due to kinetic energy spread and instabilities that disrupted hotspot formation. Notably, time-resolved neutron emission maps revealed anisotropic emission patterns, with enhanced yield along the axis of ring symmetry, suggesting directional enhancement due to geometric focusing.Comparative analysis across the three platforms indicates a clear trade-off between symmetry and realism. While HYADES predicts the highest neutron output under idealized symmetric conditions, LILAC and VORPAL highlight the important roles of asymmetries, instabilities, and kinetic effects in reducing fusion efficiency. Despite the losses observed in higher-dimensional simulations, the data confirm that a ring laser geometry is capable of delivering sufficient compression and heating to achieve measurable D-D fusion reactions. The data analysis from the integrated HYADES, LILAC, and VORPAL simulations demonstrates the viability and limitations of ring laser-induced D-D nuclear fusion. The core insight emerging from this study is that while idealized one-dimensional conditions can achieve high levels of compression and neutron yield, realistic two- and three-dimensional simulations reveal critical physical effects—such as asymmetries, hydrodynamic instabilities, and kinetic behaviors—that significantly influence the fusion performance.One of the most important observations is the sensitivity of the fusion yield to compression symmetry. HYADES simulations, which assume perfect spherical compression, predict the highest neutron output due to optimal hotspot formation and uniform density buildup. However, when ring laser geometry is modeled with spatial fidelity in LILAC and VORPAL, instabilities such as Rayleigh–Taylor growth and electron-ion thermal disequilibrium begin to reduce peak compression and thus lower the reaction rates. The slight misalignment in energy delivery observed in LILAC and the filamentation and Weibel instabilities captured by VORPAL both point to the complex interplay between laser geometry, plasma conditions, and fusion output.Despite the observed reductions in neutron yield in multidimensional simulations, the ring laser approach proves capable of achieving measurable D-D fusion under practical energy conditions. Notably, the anisotropic neutron emission observed in VORPAL provides important diagnostic signatures that can be used experimentally to validate the directional effects of ring laser compression.It is important to emphasize that each simulation code brings unique value to the analysis: HYADES provides an idealized benchmark for theoretical maximum performance, LILAC reveals the effects of geometric asymmetry on fusion uniformity, and VORPAL exposes the intricate field-particle interactions that govern real plasma behavior at the kinetic level. Taken together, these tools provide a powerful predictive framework for optimizing inertial fusion configurations.

Results and discussion

The simulation results from the HYADES, LILAC, and VORPAL codes provide a comprehensive view of the physical behavior of deuterium-deuterium (D-D) fusion under ring laser compression. Each platform captured distinct aspects of the process, from idealized hydrodynamic behavior to real-world asymmetries and kinetic instabilities. The integration of these results offers crucial insights into the effectiveness of ring laser configurations and the underlying physics of inertial confinement fusion.In the one-dimensional HYADES simulations, the ring laser pulse delivered a peak intensity of 10^{15} W/cm^2 over a duration of 1 ns to a 1 mm-radius D-D fuel pellet. The simulations predicted efficient spherical compression with minimal energy losses and highly uniform hotspot formation. The fuel was compressed from its initial density of 0.1 g/cm^3 to over 40 g/cm^3, and the core temperature reached ~12 keV (Fig. 2). Under these conditions, the neutron yield for the D-D reaction channels was estimated at approximately 1.1×10^{10} neutrons per pulse. These results highlight the theoretical maximum performance of the system under ideal symmetry.LILAC simulations introduced two-dimensional effects to account for the spatial structure of the ring laser geometry (Fig. 3). It illustrates



Figure 2. Temperature Evolution in 1D HYADES Simulation.



Figure 3. Density Profile in 2D LILAC Simulation.

the compressed D-D fuel pellet with central high-density regions and asymmetry along the axial direction, characteristic of ring laser-driven implosions.The results showed that although the ring configuration provided generally symmetric equatorial compression, axial instabilities and perturbations developed during the implosion. Rayleigh–Taylor instabilities, arising near the ablation front, disrupted the uniformity of the inward-moving shell and degraded the hotspot compactness. As a result, the peak density achieved was ~35 g/cm³, and core temperatures were reduced to approximately 9 keV. The total neutron yield dropped to about 7.8×10^9 neutrons per pulse. Nonetheless, LILAC confirmed that the ring laser could effectively compress the target and initiate significant fusion reactions, even with moderate asymmetries.The VORPAL simulations added further depth by capturing three-dimensional kinetic effects, particle dynamics, and electromagnetic field interactions. These simulations revealed the development of non-Maxwellian ion distributions and anisotropic heating due to electron acceleration near the laser-plasma interface. Self-generated electric and magnetic fields—arising from Weibel and filamentation instabilities—were observed, especially during the peak laser interaction phase (Fig. 4). These localized fields influenced ion confinement and energy transport, contributing to spatial variations in neutron emission. The average neutron yield from VORPAL was around 6.5×10^9 neutrons per pulse, with evidence of directional neutron output, particularly along the axis of ring symmetry (Fig. 5). A key finding across all simulations is the sensitivity of D-D fusion yield to symmetry and kinetic effects. The comparison shows a clear trend: as the model dimensionality increases and more realistic physics are included, neutron yield decreases due to growing asymmetries and instabilities. However, the yield remains within the same



Figure 4. Self-Generated Magnetic Fields in 3D VORPAL Simulation.



Figure 5. Time-Resolved Neutron Emission Map.

order of magnitude across all three platforms, validating the viability of the ring laser concept under non-ideal conditions.Another important observation is the directional nature of energy deposition and neutron emission in the ring configuration. This suggests that ring lasers may be tuned not only for uniform compression but also to guide fusion product emission for diagnostic or engineering purposes.The use of a D-D fuel target also introduces an advantage in terms of simplicity and reduced activation risks compared to D-T fusion, making this approach suitable for early-stage fusion research. While D-D reactions offer lower cross-sections than D-T, the results demonstrate that with sufficient compression and temperature, they can produce measurable and repeatable yields under laser-driven conditions.In summary, the simulation results confirm that ring laser-induced compression is capable of initiating significant D-D fusion and that a multi-code approach is essential for capturing the full scope of plasma dynamics, from hydrodynamic motion to kinetic field-particle interactions. The most important outcomes of this study include the identification of achievable core parameters for D-D ignition, the quantification of neutron yields under realistic conditions, and the demonstration of asymmetry and instability effects in laser-plasma coupling. These insights provide critical guidance for future experimental designs and the optimization of laser fusion schemes using alternative geometries and fusion fuels.

Conclusion

This study presents a comprehensive investigation into the feasibility of achieving nuclear fusion using a ring laser configuration with a deuterium-deuterium (D-D) fuel target. Through an integrated simulation approach using HYADES, LILAC, and VORPAL, the physical behavior of laser-driven inertial confinement was explored across one, two, and three dimensions, encompassing fluid dynamics, radiation transport, kinetic effects, and electromagnetic field evolution.The one-dimensional simulations using HYADES established a theoretical performance limit, achieving ideal compression with a peak ion temperature of approximately 12 keV, a central density of ~45 g/cm³, and a neutron yield of 1.1×10^{10} per pulse (Fig. 6). Two-dimensional LILAC simulations captured the influence of ring laser geometry and revealed moderate axial asymmetries and Rayleigh–Taylor instabilities, with the system still achieving fusion-relevant conditions of ~9 keV, ~35 g/cm³, and 7.8×10^{9} neutrons per pulse (Fig. 7). The three-dimensional VORPAL simulations confirmed the presence of Weibel and filamentation instabilities, anisotropic neutron emission, and self-generated magnetic fields, yet still demonstrated sufficient compression and heating, producing ~8.5 keV, ~30 g/cm³, and 6.5×10^{9} neutrons per pulse.The consistency of these results across all simulation platforms clearly demonstrates that fusion is indeed possible using a ring laser configuration, even in the presence of real-world asymmetries and kinetic instabilities (Fig. 8). The ring laser approach delivers sufficient energy to compress and heat a D-D fuel target to conditions necessary for significant neutron production (Fig. 9), showing the neutron yields from HYADES (1D), LILAC (2D), and VORPAL (3D) simulations. The plot highlights how dimensional complexity and symmetry affect fusion out-



Figure 6. Hotspot Pressure vs Time (HYADES Simulation).



Figure 7. Rayleigh–Taylor Instability Growth (LILAC).



Figure 8. Fusion Viability – D-D Reactivity vs Achieved Temperature.



Figure 9. D-D Fusion Yield vs Compression Symmetry.



Figure 10. Fusion-Relevant Temperature-Density Window.

put. Moreover, the directional nature of neutron emission observed in 3D simulations opens possibilities for diagnostic optimization and anisotropic fusion energy control.The insights gained here also advance the broader understanding of how spatially shaped laser fields interact with plasma to produce ignition conditions under controlled laboratory conditions (Fig. 10), highlighting the region of optimal D-D fusion reactivity. The cyan marker indicates the achieved simulation point (12 keV, 40 g/cm³), confirming it lies well within the viable fusion zone.

Significance

The significance of this study lies in its demonstration that deuterium-deuterium fusion can be achieved



Figure 11. The results from HYADES, LILAC, and VORPAL simulations over a fusion yield potential map.



Figure 12. Density of compressed D-D fuel pellets with asymmetries and kinetic instabilities.

using a ring laser configuration, offering a novel and viable alternative to conventional spherical irradiation schemes. By employing a multi-code simulation framework—spanning HYADES, LILAC, and VORPAL—the research captures the full spectrum of plasma behavior from ideal hydrodynamics to complex three-dimensional kinetic effects (Fig. 11), confirms that all three simulations achieved fusion-relevant conditions. The results confirm that even with asymmetries and instabilities, the ring laser setup consistently reaches fusion-relevant conditions, marking a step forward in both theoretical modeling and experimental feasibility (Fig. 12). The absence of excessive fast electron generation and their subsequent penetration into the fuel is a key positive outcome, as preheat would significantly hinder the compression needed for D-D ignition. The collective results strongly suggest that the ring laser configuration offers a viable pathway to achieving the extreme conditions necessary for D-D fusion, with the uniform compression contributing to the overall stability and performance of the implosion.

References

- Atzeni S, Meyer-ter-Vehn J (2004) The Physics of Inertial Fusion. Clarendon Press. https://doi.org/10.1093/acprof:oso/9780198562641.001.0001
- Azechi H (2016) A pathway to laser fusion energy in Japan. Journal of Physics: Conference Series 717: 012119. https://doi.org/10.1142/9781911299660_0039

- Bell G, Bruhwiler D, Sobol A, Ben-Zvi I, Litvinenko V, Derbenev Y (2008) VORPAL Simulations Relevant to Coherent Electron Cooling. Conf. Proc. C. 0806233: THPC085.
- Betti R, Hurricane O (2016) Inertial-confinement fusion with lasers. Nature Physics 12: pages 435–448. https://doi.org/10.1038/nphys3736
- Biedron SG, Chae YC, Dejus RJ, Faatz B, Freund HP, Milton SV, Nuhn H-D, Reiche S (2000) Multi-dimensional free-electron laser simulation codes: a comparison study. Nuclear Instruments and Methods in Physics Research – section A 445: 1–3. https://doi.org/10.1016/S0168-9002(00)00124-8
- Bingren S (2005) Core Plasma Characteristics of a Spherical Tokamak D-^{3}He Fusion Reactor. Plasma Sources Science and Technology7: 2767. https://doi.org/10.1088/1009-0630/7/2/019
- Bosch H-S, Hale GM (1992) Improved formulas for fusion cross-sections and thermal reactivities. Nuclear Fusion 32: 611. https://doi.org/10.1088/0029-5515/32/4/I07
- Cao SH, Patel D, Lees A, Stoeckl C, Rosenberg MJ, Gopalaswamy V, Wen H, Huang H, Shvydky A, Betti R, Ren C (2022) Predicting hot electron generation in inertial confinement fusion with particle-in-cell simulations.Physical Review E 106: 055214. https://doi.org/10.1103/PhysRevE.106.055214
- Colaïtis A, Follett RK, Palastro JP, Igumenschev I, Goncharov V (2019) Adaptive inverse ray-tracing for accurate and efficient modeling of cross beam energy transfer in hydrodynamics simulations. Physics of Plasmas 26: 072706. https://doi.org/10.1063/1.5108777
- Craxton R, Anderson K, Boehly T, Goncharov VN, Harding DR, Knauer JP, McCrory RL, McKenty PW, Meyerhofer DD, Myatt JF, Schmitt AJ, Sethian JD, Short RW, Skupsky S, Theobald W, Kruer WL, Tanaka K, Betti R, Collins TJB, Delettrez JA, Hu SX, Marozas JA, Maximov AV, Michel DT, Radha PB, Regan SP, Sangster TC, Seka W, Solodov AA, Soures JM, Stoeckl C, Zuegel JD (2015) Direct-drive inertial confinement fusion: A review. Physics of Plasmas 22: 110501. https://doi.org/10.1063/1.4934714
- Diels J, Arissian L (2011) Lasers: The Power and Precision of Light. Wiley-VCH. https://doi.org/10.1002/9783527640034
- Ditmire T, Zweiback J, Yanovsky VP, Cowan TE, Hays G, Wharton KB (1999) Nuclear fusion from explosions of femtosecond laser-heated deuterium clusters. Nature 398: 489–492. https://doi.org/10.1038/19037
- Drake R (2006) High-Energy-Density Physics. Springer.
- Giuffrida L, Belloni F, Margarone D, Petringa G, Milluzzo G, Scuderi V, Velyhan A, Rosinski M, Picciotto A, Kucharik M, Dostal J, Dudzak R, Krasa J, Istokskaia V, Catalano R, Tudisco S, Verona C, Jungwirth K, Bellutti P, Korn G, Cirrone GAP (2020) High-current stream of energetic α particles from laser-driven proton-boron fusion. Physical Review E 101: 013204. https://doi.org/10.1103/PhysRevE.101.013204
- Hohenberger M, Chang P, Fiksel G, Knauer JP, Betti R, Marshall FJ, Meyerhofer DD, Séguin FH, Petrasso RD (2012) Inertial confinement fusion implosions with imposed magnetic field compression using the OMEGA Laser. Physics of Plasmas 19: 056306. https://doi.org/10.1063/1.3696032
- Hurricane OA, Callahan DA, Casey DT, Celliers PM, Cerjan C, Dewald EL, Dittrich TR, Döppner T, Hinkel DE, Berzak Hopkins LF, Kline JL, Le Pape S, Ma T, MacPhee AG, Milovich JL, Pak A, Park H-S, Patel PK, Remington BA, Salmonson JD, Springer PT, Tommasini R (2014) Fuel gain exceeding unity in an inertially confined fusion implosion. Nature 506: 343–348. https://doi.org/10.1038/nature13008
- Imasaki K, Li D (2008) A new approach of laser induced nuclear fusion in plasma by intense laser propagation. Journal of Physics: Conference Series 112: 042071. https://doi.org/10.1088/1742-6596/112/4/042071
- Kodama R, Norreys PA, Mima P, Dangor AE, Evans RG, Fujita H, Kitagawa Y, Krushelnick K, Miyakoshi T, Miyanaga N, Norimatsu T, Rose SJ, Shozaki T, Shigemori K, Sunahara A, Tampo M, Tanaka KA, Toyama Y, Yamanaka T, Zepf M (2001) Fast heating of ultra-high-density plasma as a step towards laser fusion ignition. Nature 412: 798–802. https://doi.org/10.1038/35090525
- Krása J, Klír D (2020) Scaling of Laser Fusion Experiments for DD-Neutron Yield. Frontiers in Physics 8: 310. https://doi.org/10.3389/fphy.2020.00310
- Larsen J, Lane S (1994) HYADES—A plasma hydrodynamics code for dense plasma studies. Journal of Quantitative Spectroscopy and Radiative Transfer 51(1–2): 179–186. https://doi.org/10.1016/0022-4073(94)90078-7
- Lawson J (1957) Some Criteria for a Power Producing Thermonuclear Reactor. Proceedings of the Physical Society, Section B 70: 6. https://doi.org/10.1088/0370-1301/70/1/303
- Lehmberg R, Rothenberg J (2000) Comparison of optical beam smoothing techniques for inertial confinement fusion and improvement of smoothing by the use of zero-correlation masks. Journal of Applied Physics 87: 1012–1022. https://doi.org/10.1063/1.371973
- Lindl JD, Amendt P, Berger RL, Glendinning SG, Glenzer SH, Haan SW, Kauffman RL, Landen OL, Suter LJ (2004) The physics basis for ignition using indirect-drive targets on the National Ignition Facility. Physics of Plasmas 11: 339–491. https://doi.org/10.1063/1.1578638
- Madison K, Patel P, Allen M, Price D, Fitzpatrick R, Ditmire T (2004) Role of laser-pulse duration in the neutron yield of deuterium cluster targets. Physical Review A70: 053201. https://doi.org/10.1103/PhysRevA.70.053201
- Marinak MM, Kerbel GD, Gentile NA, Jones O, Munro D, Pollaine S, Dittrich TR, Haan SW (2001) Three-dimensional HYDRA simulations of National Ignition Facility targets. Physics of Plasmas 8: 2275–2280. https://doi.org/10.1063/1.1356740
- McClarren R, Ryu D, Drake R, Grosskopf M, Bingham D, Chou C-C, Fryxell B, van der Holst B, Holloway JP, Kuranz CC, Mallick B, Rutter E, Torralva BR (2011) A physics informed emulator for laser-driven radiating shock simulations. Reliability Engineering and System Safety 96(9): 1194–1207. https://doi.org/10.1016/j.ress.2010.08.012
- Michel P, Divol L, Williams EA, S Weber, Thomas CA, Callahan DA, Haan SW, Salmonson JD, Dixit S, Hinkel DE, Edwards MJ, MacGowan BJ, Lindl JD, Glenzer SH, Suter LJ (2009) Tuning the Implosion Symmetry of ICF Targets via Controlled Crossed-Beam Energy Transfer. Physical Review Letters 102: 025004. https://doi.org/10.1103/PhysRevLett.102.025004
- Moody J, Pollock B, Sio H, Strozzi DJ, Ho DD-M, Walsh CA, Kemp GE, Lahmann B, Kucheyev SO, Kozioziemski B, Carroll EG, Kroll J, Yanagisawa DK, Angus J, Bachmann B, Bhandarkar SD, Bude JD, Divol L, Ferguson B, Fry J, Hagler L, Hartouni E, Herrmann MC, Hsing W, Holunga DM, Izumi N, Javedani J, Johnson A, Khan S, Kalantar D, Kohut T, Logan BG, Masters N, Nikroo A, Orsi N, Piston K, Provencher C, Rowe A, Sater J, Skulina K, Stygar WA, Tang V, Winters SE, Zimmerman G, Adrian P, Chittenden JP, Appelbe B, Boxall A, Crilly A, O'Neill S, Davies J, Peebles J, Fujioka S (2022)

Increased Ion Temperature and Neutron Yield Observed in Magnetized Indirectly Driven D_2-Filled Capsule Implosions on the National Ignition Facility. Physical Review Letters 129: 195002. https://doi.org/10.1103/PhysRevLett.129.195002

- Nieter C, Cary J (2004) VORPAL: a versatile plasma simulation code. Journal of Computational Physics 196: 448–473. https://doi.org/10.1016/j.jcp.2003.11.004
- Nora R, Theobald W, Betti R (2015) Gigabar Spherical Shock Generation on the OMEGA Laser. Physical Review Letters 114: 045001. https://doi.org/10.1103/PhysRevLett.114.045001
- Pak A, Zylstra A, Baker K, Casey DT, Dewald E, Divol L, Hohenberger M, Moore AS, Ralph JE, Schlossberg DJ, Tommasini R, Aybar N, Bachmann B, Bionta RM, Fittinghoff D, Gatu Johnson M, Geppert Kleinrath H, Geppert Kleinrath V, Hahn KD, Rubery MS, Landen OL, Moody JD, Aghaian L, Allen A, Baxamusa SH, Bhandarkar SD, Biener J, Birge NW, Braun T, Briggs TM, Choate C, Clark DS, Crippen JW, Danly T, Durocher M, Erickson M, Fehrenbach T, Freeman M, Havre M, Hayes S, Hilsabeck T, Holder JP, Humbird KD, Hurricane OA, Izumi N, Kerr SM, Khan SF, Kim YH, Kong C, Jeet J, Kozioziemski B, Kritcher AL, Lamb KM, Lemos NC, MacGowan BJ, Mackinnon AJ, MacPhee AG, Marley EV, Meaney K, Millot M, Di Nicola J-MG, Nikroo A, Nora R, Ratledge M, Ross JS, Shin SJ, Smalyuk VA, Stadermann M, Stoupin S, Suratwala T, Trosseille C, Van Wonterghem B, Weber CR, Wild C, Wilde C, Wooddy PT, Woodworth BN, Young CV (2024) Observations and properties of the first laboratory fusion experiment to exceed a target gain of unity. Physical Review E 109: 025203. https://doi.org/10.1103/PhysRevE.109.025203
- Peng HS, Zheng ZJ, Zhang BH, Ding YK, Tang YJ, Zheng YM, Wen SH, Liu ZL, Ding YN, Tang DY, Feng J, Chen JB, Cheng JX, Miao WY, Lui SY, Jiang SE, Qi LY, Qiu LH, Yao SJ, Xu HP, Luo PQ, Yu R, Zhang YH, Chen GN, Lai DX, Zhu SP, Zhang WY, Chang TQ, He XT (2000) Direct-Drive Implosion Experiments on the SG-II Laser Facility. Journal of Fusion Energy 19: 81–85. https://doi.org/10.1023/A:1012233910891
- Post E (1967) Sagnac Effect. Reviews of Modern Physics 39: 475. https://doi.org/10.1103/RevModPhys.39.475
- Sagnac G (1913) L'éther lumineux démontré par l'effet du vent relatif d'éther dans un interféromètre en rotation uniforme. Comptes rendus 157: 708.
- Siegman A (1986) Lasers. University Science Books.
- Sudan R (2009) Inertial confinement fusion with magnetically compressed ion rings. Laser and Particle Beams 11(2): 415–422. https://doi.org/10.1017/S0263034600004997
- Tabak M, Hammer J, Glinsky ME, Kruer WL, Wilks SC, Woodworth J, Campbell EM, Perry MD, Mason RJ (1994) Ignition and high gain with ultrapowerful lasers. Physics of Plasmas 1: 1626–1634. https://doi.org/10.1063/1.870664
- Trickey W, Goncharov V, Betti R, Campbell EM, Collins TJB, Follett RK (2024) The physics of gain relevant to inertial fusion energy target designs. Physics of Plasmas 31: 012702. https://doi.org/10.1063/5.0167405
- Xuezhi W, Yinren S, Zheng G, Yanying Z, Kun Z, Gen Y, Haiyang L, Chen L, Wenjun M, Jiaer C, Xueqing Y (2020) Laser-driven ion acceleration: development and potential applications. High Power Laser and Particle Beams 32: 092002.
- Zimmerman G, Kruer W (1975) Numerical simulation of laser-initiated fusion. Comments on Plasma Physics and Controlled Fusion 2(2): 51–60.